



ODE PASTA

THE RESIN FLOOR WITH CONCRETE EFFECT.

WARM, EXCITING AND BASED ON NATURAL

BASIC COLORS. THE EARTH SETS GIVE THIS ODE

SEAMLESS FLOOR A CONTEMPORARY CONCRETE LOOK EFFECT.

Colors

The Pasta floor is mixed manually according to a fixed color concept. The mixture is then spread over the floor so that a so-called color mix is created, which results in a concrete look effect. Some parts look calm in terms of color blend or color mixing, others look busier. A sample of the Pasta floor gives only an indication of the end result; the seamless floor can always look different in practice. The Pasta floor is supplied in 18 colors as stated on our website www.odeaandevloer.nl

Characteristics

The Pasta resin floor is sustainable, 100% UV resistant, durable, sound-absorbant, liquid-tight, easy to clean and retains its elasticity.

Application

Residential houses, apartments, showrooms, shops, hotels and offices. The Pasta floor is suitable for all areas.

Cleaning

Periodic wiping, vacuuming and mopping with a damp cloth or mop is sufficient. If the Ode resin floor is cared for in accordance with our cleaning advice, its functionality and appearance will be retained for a long time

Underfloor heating

An Ode resin floor is very suitable for underfloor heating. The heat from the underfloor heating is easily transferred. This means a faster heating time and therefore lower energy costs.

Sound absorption

An Ode resin floor offers good sound insulation. Ode has developed an acoustic underlay for apartments that provides a 14 dB impact sound reduction.

Material

The Pasta resin floor is a plant-based polyurethane (PU) floor and consists of renewable, responsibly sourced raw materials based on biopolymers, extracted from plant seeds. The Pasta floor is recyclable, free from volatile organic substances and solvents, extensively tested, ISO certified and meets the strictest (inter)national building standards.

Production

The Pasta seamless floor is produced sustainably in the Netherlands. Behind our company stands Bolidt Kunststofoppassing B.V., a company with more than 50 years of global experience in the industrial market. Bolidt is innovative and sustainable.

Installation

The starting point is a level sand-cement screed, the Pasta resin floor is applied on site in 5 layers in an average layer thickness of 3 mm. Our own contractors need approx. 5 days to apply a seamless floor. After the last layer has been applied, the floor can be walked on after 12 hours and can take heavy weight after 48 hours.

Substrate

Sand-cement screeds must be installed level. The moisture percentage in the floor must not exceed 2.5%.

Anhydrite floors must be applied level. The moisture percentage in the floor must not exceed 0.5%.

Wooden floors must be finished (by third parties) with Plywood or gypsum fiber boards such as Fermacell.

The Ode seamless floor can be applied to tile floors, marble and hard stone floors, provided that they are properly secured.