



ODE PRO

THE ODE RESIN FLOOR THAT APPROACHES
THE APPEARANCE OF A TRADITIONAL CONCRETE
FLOOR THE MOST. BOLD, VIVID AND INDUSTRIAL.

Colors

The Pro floor comes in 13 solid colors with an industrial character, as stated on our website www.odeaandvloer.nl

Characteristics

The Pro resin floor is sustainable, 100% UV resistant, seamless, liquid-tight and easy to clean. Because the Pro seamless floor is applied in thinner layers, the structure of the substrate remains visible.

Application

The Pro seamless floor is perfectly suitable for showrooms, shops and offices. The Pro floor is suitable for all areas.

Cleaning

Periodic wiping, vacuuming and mopping with a damp cloth or mop is sufficient. If the Ode resin floor is cared for in accordance with our cleaning advice, its functionality and appearance will be retained for a long time.

Underfloor heating

A Pro resin floor is not suitable for underfloor heating and therefore we do not recommend the Pro floor for use in homes or apartments.

Sound absorption

A Pro resin floor does not comply with 14 dB impact sound reduction.

Material

The Pro resin floor is a plant-based polyurethane (PU) floor and consists of renewable, responsibly sourced raw materials based on biopolymers, extracted from plant seeds. The Pro floor is recyclable, free from volatile organic substances and solvents, extensively tested, ISO certified and meets the strictest (inter)national construction standards.

Production

The Pro floor is produced sustainably in the Netherlands. Behind our company stands Bolidt Kunststoftoepassing B.V., a company with more than 50 years of global experience in the industrial market. Bolidt is innovative and sustainable.

Installation

Based on a level sand-cement screed, the Pro resin floor is applied on site in 4 layers in an average layer thickness of 2 mm. Our own contractors need approx. 5 days to apply a seamless floor. After the last layer has been applied, the floor can be walked on after 12 hours and can take heavy weight after 48 hours.

Substrate

Sand-cement screeds must be installed level. The moisture percentage in the floor must not exceed 2.5%.

Anhydrite floors must be applied level. The moisture percentage in the floor must not exceed 0.5%.

Wooden floors are not suitable as a substrate for the Pro seamless floor.

The Ode seamless floor can be applied to tile floors, marble and hard stone floors, provided that they are properly secured.